



## **TYPE DB-60 (DIRECT BURIAL) TC-6 RATED FOR USE WITH 90° C WIRE**

QUEEN CITY PLASTICS Type DB-60 TC-6, (Direct Burial Duct) rigid PVC Conduit is manufactured for direct burial without encasement in concrete (also referred to as Type 2 Duct). All QUEEN CITY PLASTICS Utility Ducts are manufactured with a special high modulus compound, offering greater crush and load bearing resistance. Utility Duct should be installed in accordance with applicable parts of NEMA Bulletin - TCB-2, NEC Article 300-5 and 710-3 (b) and is manufactured to the following standards:

National Electrical Manufacturers Association (NEMA)  
American Society for Testing and Materials (ASTM)

TC-6  
F-512

### **Rigid Nonmetallic Conduit Underground No Concrete Encasement Required**

#### **20' LENGTHS**

<b>NOM SIZE</b>	<b>CATALOG NUMBER</b>	<b>O.D.</b>	<b>MIN. WALL</b>	<b>WT. 100' BELL END</b>	<b>STD. BUNDLE</b>	<b>STD. PALLET</b>
2"	1362032	2.375	.060	33	20'	2800'
3"	1363032	3.500	.092	88	20'	1760'
4"	1364032	4.500	.121	136	20'	1140'
5"	1365032	5.563	.152	192	20'	760'
6"	1366032	6.625	.182	237	20'	520'